

Product Information



DECORA

5446PJP125R26-28S45

EAN 4031582336740

Swivel castor with central lock, housing made of Polyamide, precision ball bearing in swivel head, with integrated threadguards, wheel axle with nut. Wheel centre made of Polypropylene, Tread: TENTEprene (thermoplastic rubber), grey non-marking, precision ball bearing, stem with cam hole for profile bars



Technical Data

| | |
|------------------------|----------------|
| Wheel diameter | 125 mm |
| Width of Tread | 32 mm |
| Bolt-Ø | 28 mm |
| Bolt length | 96 mm |
| Offset | 41 mm |
| Swivel Interference | 207 mm |
| Overall height | 164 mm |
| Temperature | - 10 / + 40 °C |
| Standard | EN 12530 |
| Weight | 0.8 kg |
| Load capacity | 100 kg |
| Load capacity (static) | 200 kg |
| Swivel Radius | 103.5 mm |
| Hardness of tread | A 87 Shore |

| | | | | | |
|----------------------|---|---|---|---|---|
| Roll performance | + | + | + | + | + |
| Movement noise | + | + | + | + | + |
| Attrition | + | + | + | + | + |
| Corrosion resistance | + | + | + | + | + |



reddot design award
winner

Product Information



DECORA

5446PJP125R26-28S45

EAN 4031582336740

